




Strength to BOND
Power to PROTECT


JPOXY TILE GROUT

is a high performance, easy to apply & easy to maintain three component epoxy tile grout. It is suitable for residences, pools, kitchens, bathrooms, dairy, food, chemical & pharmaceuticals manufacturing industries, and other small & large scale industries & laboratories.


JPOXY TILE GROUT APPLICATIONS




Mosaic



Kitchen



Bathroom




Stone Joints




Outdoor



Office



Floor



Swimming Pool



Vertical Surface

JPOXY TILE GROUT PROPERTIES

- Hygienic
- Easy to apply
- Glossy finish
- Water wipeable
- Long working time
- Impervious
- Non-cracking or Powdering
- Excellent mechanical properties
- Inhibits growth of stain causing mold
- Stain proof and easy to maintain
- Excellent adhesion to substrate
- Good Chemical Resistance
- Durable, Hygienic and attractive joints
- Anti-sag (For Vertical Applications)

JPOXY POLYMERS LLP

Plot No. 25 of Survey No. 435/ Part-2, Shubh Laxmi Industrial Estate, Village: Moraiya, Taluka: Sanand, Dist.: Ahmedabad – 382213
Tel: +91-76008 01235 | Email: support@jpoxypolymers.com | Website: www.jpoxypolymers.com



PACKAGING

JPOXY tile grout is a 3 component tile grout
Wide range of colors are available to choose from



THEORETICAL COVERAGE CHART

Approximate Sq Ft Coverage Per kg of Jpoxyl Tile Grout

TILE SIZE X THICKNESS	JOINT WIDTH							
	1.5mm	2mm	3mm	4mm	6mm	8mm	10mm	12mm
in mm								
100x100x3	65-70	50-55	35-40	25-30	15-20	10-15	10-15	10-15
150x150x4	75-80	60-65	40-45	30-35	20-25	15-20	10-15	10-15
200x150x5	70-75	60-65	35-40	25-30	15-20	10-15	10-15	10-15
150x300x6	65-70	50-55	35-40	25-30	15-20	10-15	10-15	10-15
300x300x6	100-105	75-80	50-55	40-45	25-30	20-25	15-20	10-15
450x300x7	105-110	80-85	50-55	40-45	25-30	20-25	15-20	10-15
600x450x8	130-135	100-105	65-70	50-55	30-35	25-30	20-25	15-20
600x600x8	150-155	115-120	75-80	55-60	40-45	30-35	20-25	20-25
600x900x11	130-135	100-105	65-70	50-55	30-35	25-30	20-25	15-20
900x900x12	150-155	115-120	75-80	55-60	40-45	30-35	25-30	20-25

Quantities shown are approximate and are given for estimating purpose only. Actual job site coverage may vary.

APPLICATION STEPS



Part A + Part B + Part C



Mix According To The Specified Ratio



Apply Grout With Float



Lightly Clean Off Excess Grout With Wet Sponge



Remove Haze With Cheesecloth



Allow For Sufficient Curing

*Actual color may vary, For life-like color, contact support team

DISCLAIMER: All recommendation for use of our product, whether given by us in writing, verbally, or to be implied from the results of test carried out by us are based on current state of our knowledge. The buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose.

JPOXY POLYMERS LLP

Plot No. 25 of Survey No. 435/ Part-2, Shubh Laxmi Industrial Estate, Village: Moraiya, Taluka: Sanand, Dist.: Ahmedabad – 382213
Tel: +91-76008 01235 | Email: support@jpoxypolymers.com | Website: www.jpoxypolymers.com

FLOORING & COATINGS | **TILE GROUT** | TOOLING & COMPOSITES | PROTECTIVE COATINGS | ADHESIVE | INJECTION GROUT | MACHINE FOUNDATION GROUT | MARBLE & STONE | RESIN ART